









Properties	
Base Construction	Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	Brushed Nickel
Finish CCT	· · · · · · · · · · · · · · · · · · ·
	Brushed Nickel
CCT	Brushed Nickel
CCT Finish Options	Brushed Nickel 3000K
CCT Finish Options  Black	Brushed Nickel 3000K Gold/Brass
CCT  Finish Options  Black Bronze	Brushed Nickel 3000K  Gold/Brass ORB

## Options

Size	Dimensions	Wattage	Voltage	Lumens
DRBV-14	L:14.5" H:7"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
DRBV-21	L:21.5" H:7"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
DRBV-26	L:26" H:7"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
DRBV-38	L:38" H:7"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
DRBV-50	L:50" H:7"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3900/5200

Not seeing what you're looking for?

Contact us!

info@asllighting.com