





Properties		
Base Construction	Cold-rolled Steel	
Lens	Acrylic	
Application	Vanity	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V-277V (non dimming)	
Finish	Brushed Nickel	
CCT	3000K	
Finish Options		
□ Black	☐ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	☐ White	
<b>CCT Options</b>		
CCT	2700K/3000K/3500k/4000K/5000K	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
DSZ-24	L:24.5" H:5.7"	15/23	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2990
DSZ-36	L:36.5" H:5.7"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/4680
DSZ-48	L:48.5" H:5.7"	20/25/35/4 6	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/4550/598 0

Not seeing what you're looking for?

Contact us!

info@asllighting.com