









Properties				
Base Construction	Steel			
Lens	Acrylic			
Application	Vanity			
Location	Damp			
CRI	80			
Life Hours	50,000			
Light Source	Integrated LED			
Standard Selection				
Voltage	120V (non dimming)			
Voltage Finish	120V (non dimming) Brushed Nickel			
Finish	Brushed Nickel			
Finish	Brushed Nickel			
Finish CCT Finish Options	Brushed Nickel			
Finish CCT Finish Options Black	Brushed Nickel 3000K Gold/Brass			
Finish CCT Finish Options Black Bronze	Brushed Nickel 3000K Gold/Brass ORB			

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBC-25	L:25.5" H:4.75"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VBC-37	L:37.5" H:4.75"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
VBC-49	L:49.5" H:4.75"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200

Not seeing what you're looking for?

Contact us!

info@asllighting.com