





| Base Construction | Cold-rolled Steel |
|-----------------------------|------------------------------|
| Lens | Acrylic |
| Application | Vanity |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Standard Selection Voltage | 120V-277V (non dimming |
| Finish | Brushed Nicke |
| | |
| CCT | 3CCT - 3000K / 3500K / 4000K |
| CCT Finish Options | 3CCT - 3000K / 3500K / 4000K |
| | 3CCT - 3000K / 3500K / 4000K |
| Finish Options | |
| Finish Options Black | _ |

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|----------------|----------|---|----------------|
| VBDC-25 | L:25.8" H:4.4" | 10/18/20 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/2340/2600 |
| VBDC-37 | L:37.6" H:4.4" | 15/24/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3120/3250 |
| VBDC-49 | L:49.4" H:4.4" | 20/25/36 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/4680 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com