



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3CCT - 3000K / 3500K / 4000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

CCT 2700K/3000K/3500k/4000K/5000K/3CCT - 3000K / 3500K / 4000K

### Options

Size	Dimensions	Wattage	Voltage	Lumens
VBDC-25	L:25.8" H:4.4" E:4.1"	10/18/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2340/2600
VBDC-49	L:49.4" H:4.4" E:4.1"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4680

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)