









Properties			
Base Construction	Cold-rolled Steel		
Lens	Acrylic		
Application	Vanity		
Location	Damp		
CRI	80		
Life Hours	50,000		
Light Source	Integrated LED		
Standard Selection			
Voltage	120V-277V (non dimming)		
Finish	Brushed Nickel		
CCT	3000K		
Finish Options			
□ Black	☐ Gold/Brass		
□ Bronze	□ ORB		
☐ Brushed Nickel	□ White		
CCT Options	□ White		

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBEB-25	L:24.8" H:4.7"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBEB-37	L:36.8" H:4.7"	15/23/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3250
VBEB-49	L:48.5" H:4.7"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4680

Not seeing what you're looking for?

Contact us!

info@asllighting.com