



ADA Compliant

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBEB-25	L:24.8" H:4.7"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBEB-37	L:36.8" H:4.7"	15/23/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3250
VBEB-49	L:48.5" H:4.7"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4680

Not seeing what you're looking for?

Contact us!

info@asllighting.com