



ADA Compliant

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- Black
- Gold/Brass
- Bronze
- ORB
- Brushed Nickel
- White

CCT Options

CCT	2700K/3000K/3500K/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBH-22	L:22" H:4.8"	11	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1430
VBH-34	L:34" H:4.8"	18	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2340
VBH-46	L:46" H:4.8"	23	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2990

Not seeing what you're looking for?

Contact us!

info@asllighting.com