







Properties	
Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3CCT - 3000K / 3500K / 4000K
Finish Options	
Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
CCT Options	
CCT	3000K/3CCT - 3000K / 3500K / 4000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBHE-22	L:22" H:4.7"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBHE-34	L:34" H:4.7"	15/23/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3250
VBHE-46	L:46" H:4.7"	20/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4550

Not seeing what you're looking for?

Contact us!

info@asllighting.com