







Properties		
Base Construction	Cold-rolled Steel	
Lens	Acrylic	
Application	Vanity	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V-277V (non dimming)	
Finish	Brushed Nickel	
CCT	3CCT - 3000K / 3500K / 4000K	
Finish Options		
□ Black	□ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	□ White	
CCT Options		
CCT	3CCT - 3000K / 3500K / 4000K	

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBHE-22	L:22" H:4.7"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBHE-34	L:34" H:4.7"	15/23/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3250
VBHE-46	L:46" H:4.7"	20/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4550

Not seeing what you're looking for?

Contact us!

info@asllighting.com