







Properties	
Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K
Finish Options	
□ Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
<b>CCT Options</b>	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
VBJ-24	L:23.75" H:4.25"	10/17/19/2 0/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/2210/2470/260 0/3250
VBJ-36	L:36" H:4.25"	15/23/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2990/3250
VBJ-48	L:48" H:4.25"	20/25/35	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/4550

CCT

Options EMG - Emergency

Not seeing what you're looking for?

2700K/3000K/3500k/4000K/5000K

Contact us!

info@asllighting.com