







Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V-277V (non dimming)
Finish	ORB
CCT	3000K
Finish Options	

## CCT Options

CCT	2700K/3000K/3500k/4000K/5000K

☐ Gold/Brass

□ ORB

□ White

## Options

Size	Dimensions	Wattage	Voltage	Lumens
VBJF-24	L:24" H:4.8"	17	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2210
VBJF-36	L:36" H:4.8"	24	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3120
VBJF-48	L:48" H:4.8"	36	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	4680

**Properties** 

□ Black

□ Bronze

☐ Brushed Nickel

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com