







Properties		
Base Construction	Cold-rolled Steel	
Lens	Acrylic	
Application	Vanity	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V-277V (non dimming)	
Finish	Brushed Nickel	
ССТ	3000K	
Finish Options		
□ Black	□ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	□ White	
CCT Options		
CCT	2700K/3000K/3500k/4000K/5000K	

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBJG-24	L:24" H:4.3"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
VBJG-36	L:36" H:4.3"	15/22/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2860/3250
VBJG-48	L:48" H:4.3"	20/25/32	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4160

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com