



ADA Compliant

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Aluminum
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- | | |
|---|---|
| <input type="checkbox"/> Black | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> White |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> Brushed Aluminum |
| <input type="checkbox"/> Gold/Brass | |

CCT Options

CCT	3CCT - 3000K / 3500K / 4000K
-----	------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBOM-22	L:22" H:4.7" E:3.2"	18	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2340
VBOM-34	L:34" H:4.7" E:3.2"	23	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2990
VBOM-46	L:46" H:4.7" E:3.2"	35	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550

Not seeing what you're looking for?

Contact us!

info@asllighting.com