



ADA Compliant

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	BLACK
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	3CCT - 3000K / 3500K / 4000K
-----	------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBOMB-22	L:22" H:4.8"	17	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2210
VBOMB-34	L:34" H:4.8"	22	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2860
VBOMB-46	L:46" H:4.8"	34	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4420

Not seeing what you're looking for?

Contact us!

info@asllighting.com