









Properties	
Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K
Finish Options	
□ Black	□ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
CCT Options	

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBRA-12	L:12" H:4.5"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
VBRA-24	L:24" H:4.5"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VBRA-36	L:36" H:4.5"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
VBRA-48	L:48" H:4.5"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200

CCT

Options

BBX-Backbox W 3/4" Conduit hole EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

2700K/3000K/3500k/4000K/5000K

Contact us!

info@asllighting.com