







Properties		
Base Construction	Steel	
Lens	Acrylic	
Application	Vanity	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V (non dimming)	
Finish	Brushed Nickel	
CCT	3000K	
<b>Finish Options</b>		
□ Black	☐ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	☐ White	
<b>CCT Options</b>		
CCT	2700K/3000K/3500k/4000K/5000K	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
VBRD-27	L:27" H:5"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
VBRD-37	L:37" H:5"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900

## **Options**

BBX-Backbox W

3/4" Conduit hole

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com