







Properties	
Base Construction	Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K
Finish Options	
□ Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
CCT Options	
CCT	2700K/3000K/3500k/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBW-22	L:22" H:4.75"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
VBW-34	L:34.5" H:4.75"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
VBW-46	L:46" H:4.75"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200

Options

BBX-Backbox W 3/4" Conduit hole EMG - Emergency OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming Not seeing what you're looking for?

Contact us!

info@asllighting.com