







Properties		
Base Construction	Steel	
Lens	Acrylic	
Application	Vanity	
Location	Damp	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V-277V (non dimming)	
Finish	Brushed Nickel	
CCT	3000K	
Finish Options		
□ Black	☐ Gold/Brass	
□ Bronze	□ ORB	
☐ Brushed Nickel	□ White	
<b>CCT Options</b>		
CCT	2700K/3000K/3500k/4000K/5000K	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
VBX-25	L:25" H:4.8"	10/17/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/2210/3250
VBX-37	L:37" H:4.8"	15/23/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2990/3900
VBX-49	L:49" H:4.8"	25/30/35/4 0	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3250/3900/4550/520 0

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com