



Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Vanity |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|------------------------|-------------|---|---------------------|
| VBX-25 | L:25" H:4.8" E:3.9" | 10/17/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/2210/3250 |
| VBX-49 | L:49" H:4.8" E:3.9" | 25/30/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3250/3900/4550/5200 |

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com