



### Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Glass             |
| Application       | Vanity            |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

### Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Brushed Nickel     |
| CCT     | 3000K              |

### Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size    | Dimensions   | Wattage  | Voltage                                                                                                           | Lumens         |
|---------|--------------|----------|-------------------------------------------------------------------------------------------------------------------|----------------|
| VBXB-22 | L:22" H:4.7" | 15/19/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2470/3250 |
| VBXB-36 | L:36" H:4.7" | 20/23/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/2990/3900 |

### Options

EMG - Emergency

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)