









Properties			
Base Construction	Cold-rolled Steel		
Lens	Glass		
Application	Vanity		
Location	Damp		
CRI	80		
Life Hours	50,000		
Light Source	Integrated LED		
Standard Selection			
\/altaaa	120V-277V (non dimming)		
Voltage	120V-277V (non dimming)		
Finish	120V-277V (non dimming) Brushed Nickel		
	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Finish	Brushed Nickel		
Finish	Brushed Nickel		
Finish CCT Finish Options	Brushed Nickel		
Finish CCT Finish Options Black	Brushed Nickel 3000K Gold/Brass		
Finish CCT Finish Options Black Bronze	Brushed Nickel 3000K Gold/Brass ORB		

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBXB-22	L:22" H:4.7"	15/19/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2470/3250
VBXB-36	L:36" H:4.7"	20/23/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/2990/3900

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com