







Properties					
Base Construction	Steel				
Lens	Acrylic				
Application	Vanity				
Location	Damp				
CRI	80				
Life Hours	50,000				
Light Source	Integrated LED				
Standard Selection					
Voltage	120V Triac dimming				
Voltage Finish	120V Triac dimming Brushed Nickel				
Finish	Brushed Nickel				
Finish	Brushed Nickel				
Finish CCT Finish Options	Brushed Nickel 3000K				
Finish CCT Finish Options Black	Brushed Nickel 3000K Gold/Brass				
Finish CCT Finish Options Black Bronze	Brushed Nickel 3000K Gold/Brass ORB				

Options

Size	Dimensions	Wattage	Voltage	Lumens
VNAL-31	L:31" H:4"	20/25/30/3 5	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900/455
VNAL-43	L:43" H:4.25"	25/30/35/4 0	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/3900/4550/520 0

Options

BBX-Backbox W 3/4" Conduit hole EMG - Emergency Not seeing what you're looking for?

Contact us!

info@asllighting.com