



ADA Compliant

Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Vanity |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V Triac dimming |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|---------------|-------------|---|---------------------|
| VNAL-31 | L:31" H:4" | 20/25/30/35 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900/4550 |
| VNAL-43 | L:43" H:4.25" | 25/30/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3250/3900/4550/5200 |

Options

- BBX-Backbox W
- ¾" Conduit hole
- EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com