



Properties

Base Construction	Steel
Lens	Acrylic
Application	Over Bed
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP & DOWN WITH 4WAY PULL CHAIN

Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	Brushed Nickel
CCT	3500k

Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> Gold/Brass
<input type="checkbox"/> Bronze	<input type="checkbox"/> ORB
<input type="checkbox"/> Brushed Nickel	<input type="checkbox"/> White

CCT Options

CCT	2700K/3000K/3500k/4000K
-----	-------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
CCV13-24	L:24" H:5.5"	20/24/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3120/3900
CCV13-36	L:36" H:5.5"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
CCV13-48	L:48" H:5.5"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

Options

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com