











Properties

Steel
Acrylic
Over Bed
Damp
80
50,000
Integrated LED
UP & DOWN WITH 4WAY PULL CHAIN
120V-277V 0-10 dimming
Brushed Nickel
3500k
□ Gold/Brass
□ ORB
□ White

Options

Size	Dimensions	Wattage	Voltage	Lumens
CCV13-24	L:24" H:5.5"	20/24/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3120/3900
CCV13-36	L:36" H:5.5"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
CCV13-48	L:48" H:5.5"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

CCT

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

2700K/3000K/3500k/4000K