



Properties

| | |
|-------------------|--------------------------------|
| Base Construction | Steel |
| Lens | Glass |
| Application | Over Bed |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Light Direction | UP & DOWN WITH 4WAY PULL CHAIN |

Standard Selection

| | |
|---------|------------------------|
| Voltage | 120V-277V 0-10 dimming |
| Finish | Bronze |
| CCT | 3500k |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------|
| CCT | 2700K/3000K/3500k/4000K |
|-----|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|------------|----------|---|----------------|
| CCV32-24 | L:24" H:6" | 20/24/30 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3120/3900 |
| CCV32-36 | L:36" H:6" | 20/30/40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3900/5200 |
| CCV32-48 | L:48" H:6" | 30/46/55 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3900/5980/7150 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com