









Properties	
Base Construction	Steel
Lens	Glass
Application	Over Bed
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP & DOWN WITH 4WAY PULL CHAIN
Standard Selection	
Voltage	120V-277V 0-10 dimming
Finish	Bronze
CCT	3500k
Finish Options	
□ Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
□ Brushed Nickel CCT Options	□ White

Options

Size	Dimensions	Wattage	Voltage	Lumens
CCV32-24	L:24" H:6"	20/24/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3120/3900
CCV32-36	L:36" H:6"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
CCV32-48	L:48" H:6"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

Options

EMG - Emergency OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming Not seeing what you're looking for?

Contact us!

info@asllighting.com