







Properties			
Base Construction	Steel		
Lens	Fabric		
Application	Over Bed		
Location	Damp		
CRI	80		
Life Hours	50,000		
Light Source	Integrated LED		
Light Direction	UP & DOWN WITH 4WAY PULL CHAIN		
Standard Selection			
Voltage	120V-277V 0-10 dimming		
CCT	3500k		
Fabric Finish			
☐ Chocolate Linen	☐ Jute Linen		
☐ Grey Linen	☐ White Linen		
Finish Options			
□ Black	☐ Gold/Brass		
□ Bronze	□ ORB		
☐ Brushed Nickel	☐ White		
CCT Options			
ССТ	2700K/3000K/3500k/4000K		

Options

Size	Dimensions	Wattage	Voltage	Lumens
OBCB-36	L:36" H:7"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
OBCB-48	L:48" H:7"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com