











Properties

•			
Base Construction	Steel		
Lens	Acrylic		
Application	Over Bed		
Location	Damp		
CRI	80		
Life Hours	50,000		
Light Source	Integrated LED		
Light Direction	UP & DOWN WITH 4WAY PULL CHAIN		
Standard Selection			
Voltage	120V-277V 0-10 dimming		
Finish	Brushed Nickel		
ССТ	3500k		
Finish Options			
□ Black	☐ Gold/Brass		
_			
□ Bronze	□ ORB		

CCT Options

CCT 2700K/3000K/3500k/4000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFSB-24	L:24" H:6"	20/24/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3120/3900
RFSB-36	L:36" H:6"	20/30/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3900/5200
RFSB-48	L:48" H:6"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

Options

EMG - Emergency OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming Not seeing what you're looking for?

Contact us!

info@asllighting.com