







Properties		
Base Construction	Steel	
Lens	Acrylic	
Application	Sconce	
Location	Wet	
CRI	80	
Life Hours	50,000	
Light Source	Integrated LED	
Standard Selection		
Voltage	120V (non dimming)	
Finish	Bronze	
CCT	3000K	
Finish Options		
□ Black	☐ Gold/Brass	
□ Bronze	□ White	
☐ Brushed Nickel		
<b>CCT Options</b>		
CCT	2700K/3000K/3500k/4000K/5000K	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BCFW-12	W:7" H:12"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
BCFW-15	W:7" H:15"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
BCFW-18	W:7" H:18"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCFW-24	W:7" H:24"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCFW-30	W:8" H:30"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCFW-42	W:9" H:42"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3900/4550/5200

Options

BBX-Backbox W 3/4" Conduit hole OS - Occupancy Sensor Not seeing what you're looking for?

Contact us!

info@asllighting.com