



ADA Compliant

### Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V (non dimming)
Finish	Bronze
CCT	3000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- White

### CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
BCFW-12	H:12" W:7" E:3"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
BCFW-15	H:15" W:7" E:3"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BCFW-18	H:18" W:7" E:3"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BCFW-24	H:24" W:7" E:3"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BCFW-30	H:30" W:8" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BCFW-42	H:42" W:9" E:3"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/4550/5200

## Options

BBX-Backbox W

¾" Conduit hole

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)