50,000









| Base Construction | Cold-rolled Steel |
|-------------------|-------------------|
| Lens | Acrylic |
| Application | Sconce |
| Location | Wet |
| CRI | 80 |

Light Source Integrated LED

Standard Selection

Properties

Life Hours

| Voltage | Voltage 120V-277V (non dimmin | |
|---------|-------------------------------|--|
| Finish | Black | |
| CCT | 3000K | |

Finish Options

| ☐ Black | ☐ Gold/Brass |
|----------|--------------|
| □ Bronze | □ White |

☐ Brushed Nickel

CCT Options

CCT 2700K/3000K/3500k/4000K/5000K

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|----------------|----------|---|----------------|
| BCHW-15 | W:8.3" H:14.6" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| BCHW-24 | W:8.3" H:24" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3250 |

Options

BBX-Backbox W 3/4" Conduit hole

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com