







# **Properties**

	•	
Ва	ase Construction	Cold-rolled Steel
Le	ens	Acrylic
Ap	pplication	Sconce
Lo	ocation	Wet
CI	રા	80
Lif	e Hours	50,000
Li	ght Source	Integrated LED
04	and and Calcation	

#### **Standard Selection**

Voltage	120V-277V (non dimming)
Finish	Black
CCT	3000K

### **Finish Options**

□ Black	☐ Gold/Brass
☐ Bronze	□ White
☐ Brushed Nickel	

## **CCT Options**

CCT 2700K/3000K/3500k/4000K/5000K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BCHW-15	W:8.3" H:14.6"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
BCHW-24	W:8.3" H:24"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250

#### **Options**

PC - Photo Control

BBX-Backbox W
3/4" Conduit hole
EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com