







#### **Properties**

| Base Cons   | struction | Stainless Steel |
|-------------|-----------|-----------------|
| Lens        |           | Acrylic         |
| Application | n         | Sconce          |
| Location    |           | Wet             |
| CRI         |           | 80              |
| Life Hours  | ;         | 50,000          |
| Light Sour  | rce       | Integrated LED  |

#### **Standard Selection**

| Voltage | 120V-277V (non dimming)      |
|---------|------------------------------|
| Finish  | Black                        |
| CCT     | 3CCT - 3000K / 3500K / 4000K |

### **Finish Options**

| □ Black          | ☐ Gold/Brass |
|------------------|--------------|
| □ Bronze         | □ ORB        |
| ☐ Brushed Nickel | ☐ White      |

## **CCT Options**

CCT 2700K/3500k/3CCT - 3000K / 3500K / 4000K

# Options

| Size   | Dimensions     | Wattage  | Voltage   | Lumens         |
|--------|----------------|----------|---|----------------|
| BCJ-12 | W:6.1" H:11.8" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950/2600 |
| BCJ-18 | W:6" H:18"     | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2600/3250 |
| BCJ-24 | W:6" H:24"     | 15/23/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2990/3900 |
| BCJ-30 | W:6" H:30"     | 20/28/40 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3640/5200 |

**Options** 

BBX-Backbox W 3/4" Conduit hole

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com