



Properties

Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Black
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- | | |
|---|-------------------------------------|
| ☐ Black | ☐ Gold/Brass |
| ☐ Bronze | ☐ ORB |
| ☐ Brushed Nickel | ☐ White |

CCT Options

CCT	2700K/3500k/3CCT - 3000K / 3500K / 4000K
-----	--

Options

Size	Dimensions	Wattage	Voltage	Lumens
BCJ-12	W:6.1" H:11.8"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BCJ-18	W:6" H:18"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BCJ-24	W:6" H:24"	15/23/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3900
BCJ-30	W:6" H:30"	20/28/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3640/5200

Options

BBX-Backbox W
¾" Conduit hole
EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming
PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com