



ADA Compliant

## Properties

Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## Standard Selection

Voltage	120V-277V (non dimming)
Finish	ORB
CCT	3CCT - 3000K / 3500K / 4000K

## Finish Options

- Bronze
- ORB
- Brushed Nickel
- White
- Gold/Brass

## CCT Options

CCT	2700K/3500k/3CCT - 3000K / 3500K / 4000K
-----	--

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BCJ-12	W:6.1" H:11.8"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BCJ-18	W:6" H:18"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BCJ-24	W:6" H:24"	15/23/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3900
BCJ-30	W:6" H:30"	20/28/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3640/5200

## Options

- BBX-Backbox W
- ¾" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)