



ADA Compliant

Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
Finish	ORB
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- Black
- Gold/Brass
- Bronze
- ORB
- Brushed Nickel
- White

CCT Options

CCT	2700K/3000K/3500K/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
BCJBW-10	W:7" H:10"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600
BCJBW-15	W:7" H:15"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BCJBW-18	W:7" H:18"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BCJBW-24	W:7" H:24"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BCJBW-30	W:9" H:30"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BCJBW-42	W:9" H:42"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/4550/5200

Options

BBX-Backbox W

¾" Conduit hole

OS - Occupancy Sensor

Not seeing what you're looking for?

Contact us!

info@asllighting.com