







## **Properties**

	Base Construction	Aluminum
	Lens	Acrylic
	Application	Sconce
	Location	Wet
	CRI	80
	Life Hours	50,000
	Light Source	Integrated LED

## **Standard Selection**

CCT

Voltage	120V Triac dimming				
Finish	ORB				
CCT	3CCT - 3000K / 3500K / 4000K				
Finish Ontions					

Finish Options	
□ Black	□ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
CCT Options	

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BCJBW-10	W:7" H:10"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950/2600
BCJBW-15	W:7" H:15"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
BCJBW-18	W:7" H:18"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCJBW-24	W:7" H:24"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCJBW-30	W:9" H:30"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCJBW-42	W:9" H:42"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3900/4550/5200

**Options** 

BBX-Backbox W 3/4" Conduit hole OS - Occupancy Sensor Not seeing what you're looking for?

2700K/3000K/3500k/4000K/5000K

Contact us!

info@asllighting.com