



ADA Compliant

## Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Aluminum       |
| Lens              | Acrylic        |
| Application       | Sconce         |
| Location          | Wet            |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

## Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | ORB                |
| CCT     | 3000K              |

## Finish Options

- |                                         |                                     |
|-----------------------------------------|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500K/4000K/5000K |
|-----|-------------------------------|

## Options

| Size     | Dimensions | Wattage  | Voltage                                                                                                           | Lumens         |
|----------|------------|----------|-------------------------------------------------------------------------------------------------------------------|----------------|
| BCJBW-10 | W:7" H:10" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950/2600 |
| BCJBW-15 | W:7" H:15" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2600/3250 |
| BCJBW-18 | W:7" H:18" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCJBW-24 | W:7" H:24" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCJBW-30 | W:9" H:30" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCJBW-42 | W:9" H:42" | 30/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 3900/4550/5200 |

## Options

BBX-Backbox W

¾" Conduit hole

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)