



## Properties

|                   |                 |
|-------------------|-----------------|
| Base Construction | Stainless Steel |
| Lens              | Acrylic         |
| Application       | Sconce          |
| Location          | Wet             |
| CRI               | 80              |
| Life Hours        | 50,000          |
| Light Source      | Integrated LED  |

## Standard Selection

|         |                    |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish  | Brushed Nickel     |
| CCT     | 3000K              |

## Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Brushed Nickel
- ☐ Gold/Brass
- ☐ ORB
- ☐ White

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

## Options

| Size     | Dimensions | Wattage  | Voltage                                                                                                           | Lumens         |
|----------|------------|----------|-------------------------------------------------------------------------------------------------------------------|----------------|
| BCRAW-12 | W:6" H:12" | 10/15    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950      |
| BCRAW-15 | W:6" H:15" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2600/3250 |
| BCRAW-18 | W:6" H:18" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCRAW-24 | W:6" H:24" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCRAW-30 | W:8" H:30" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900 |
| BCRAW-42 | W:8" H:42" | 30/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 3900/4550/5200 |

## Options

BBX-Backbox W

¾" Conduit hole

OS - Occupancy Sensor

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)