







## **Properties**

Properties	
Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection  Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K
Finish Options	
□ Black	□ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BCRAW-12	W:6" H:12"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
BCRAW-15	W:6" H:15"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
BCRAW-18	W:6" H:18"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCRAW-24	W:6" H:24"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCRAW-30	W:8" H:30"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BCRAW-42	W:8" H:42"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3900/4550/5200

**CCT Options** 

CCT

**Options** 

BBX-Backbox W 3/4" Conduit hole OS - Occupancy Sensor Not seeing what you're looking for?

2700K/3000K/3500k/4000K/5000K

Contact us!

info@asllighting.com