Integrated LED











Properties Stainless Steel **Base Construction** Acrylic Lens Application Sconce Location Wet CRI 80 Life Hours 50,000

Standard Selection

Light Source

age 120V (non dimm	ning)
sh Brushed N	ickel
30	000K

Finish Options	
□ Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	□ White
CCT Options	

CCT 2700K/3000K/3500k/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
BSCW-12	W:4" H:12"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
BSCW-15	W:4" H:15"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
BSCW-18	W:4" H:18"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BSCW-24	W:4" H:24"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BSCW-30	W:6" H:30"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
BSCW-42	W:6" H:42"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/4550/5200

Options

Not seeing what you're looking for?

BBX-Backbox W

3/4" Conduit hole

EMG - Emergency

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

Contact us! info@asllighting.com