









•	
Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## **Standard Selection**

**Properties** 

Voltage	120V (non dimming)
Finish	Brushed Nickel
ССТ	3000K

Finish Options	
_	_
Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	☐ White
CCT Options	
CCT	2700K/3000K/3500k/4000K/5000K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
BSLAW-12	W:4" H:12"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
BSLAW-15	W:4" H:15"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2600/3250
BSLAW-18	W:4" H:18"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BSLAW-24	W:4" H:24"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BSLAW-30	W:6" H:30"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	2600/3250/3900
BSLAW-42	W:6" H:42"	30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3900/4550/5200

**Options** 

BBX-Backbox W 3/4" Conduit hole OS - Occupancy Sensor Not seeing what you're looking for?

Contact us!

info@asllighting.com