



Properties

| | |
|-------------------|-----------------|
| Base Construction | Stainless Steel |
| Lens | Acrylic |
| Application | Sconce |
| Location | Wet |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|--------------------|----------|---|----------------|
| BSLDW-12 | H:12" W:4" E:4" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
| BSLDW-15 | H:15" W:4" E:4" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3250 |
| BSLDW-18 | H:18" W:4" E:4" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| BSLDW-24 | H:24" W:4" E:4" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| BSLDW-30 | H:30" W:6" E:4" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| BSLDW-42 | H:42" W:6" E:4" | 30/35/40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3900/4550/5200 |

Options

BBX-Backbox W

¾" Conduit hole

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com