



Properties

Base Construction	Stainless Steel
Lens	Acrylic
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- Black
- Gold/Brass
- Bronze
- ORB
- Brushed Nickel
- White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
CCS35BW-15	H:15" W:13" E:4"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250
CCS35BW-18	H:18" W:15" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900
CCS35BW-24	H:24" W:20" E:4"	20/25/30	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/3900

Options

- BBX-Backbox W
- ¾" Conduit hole
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- PC - Photo Control

Not seeing what you're looking for?

Contact us!

info@asllighting.com