



### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Polycarbonate  |
| Lens              | Polycarbonate  |
| Application       | Sconce         |
| Location          | Wet            |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Bronze                  |
| CCT     | 3000K                   |

### Finish Options

- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size    | Dimensions               | Wattage | Voltage   | Lumens |
|---------|--------------------------|---------|---|--------|
| CMXR-11 | H:11" W:6.75"<br>E:5.25" | 13/20   | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1690   |

### Options

- EMG+BBX-Emergency + Backbox W
- ¾" Conduit hole
- PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)