



### Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Die Cast Aluminum |
| Lens              | Glass             |
| Application       | Sconce            |
| Location          | Wet               |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |
| Light Direction   | DOWN              |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black                   |
| CCT     | 3000K                   |

### Finish Options

- ☐ Black
 ☐ Brushed Nickel
 ☐ Gold/Brass
- ☐ ORB
 ☐ White

### CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

### Options

| Size   | Dimensions    | Wattage | Voltage                                                                                                           | Lumens |
|--------|---------------|---------|-------------------------------------------------------------------------------------------------------------------|--------|
| CTQA-8 | W:4.5" H:8.3" | 9       | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1170   |

### Options

PC - Photo Control

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)