80

Integrated LED







PropertiesBase ConstructionDie Cast AluminumLensGlassApplicationSconceLocationWet

Life Hours 50,000

Standard Selection

Light Source

CRI

Voltage	120V-277V (non dimming)	
Finish	Bronze	
CCT	5000K	

Finish Options

□ Bronze □ ORB

☐ Brushed Nickel ☐ White

CCT Options

CCT 2700K/3000K/3500k/4000K/5000K/5700K

Options

Size	Dimensions	Wattage	Voltage	Lumens
DSKD-14	W:14.12" H:9"	12/24/36/4 8/60/72	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/624 0/7800/9360
DSKD-18	W:18.12" H:9"	12/24/36/4 8/60/72/84/ 96	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/624 0/7800/9360/10920/ 12480

Options

EMG - Emergency
OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com