



Properties

Base Construction	Die Cast Aluminum
Lens	Glass
Application	Sconce
Location	Wet
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Bronze
CCT	5000K

Finish Options

- | | |
|---|-------------------------------------|
| ☐ Black | ☐ Gold/Brass |
| ☐ Bronze | ☐ ORB |
| ☐ Brushed Nickel | ☐ White |

CCT Options

CCT	2700K/3000K/3500K/4000K/5000K/5700K
-----	-------------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
DSKD-14	W:14.12" H:9"	12/24/36/48/60/72	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/6240/7800/9360
DSKD-18	W:18.12" H:9"	12/24/36/48/60/72/84/96	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/3120/4680/6240/7800/9360/10920/12480

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com